# Classic Series Aero Rain Shower

#### **FEATURES**

- Air injected AeroJet+™ techonology
- 2.0 gpm (7.5 lpm) maximum flow rate
- 12" diameter spray face
- Rubber nozzles to prevent limescale build up



#### **COLORS/FINISHES**

#CP Polished Chrome #BN Brushed Nickel #PN Polished Nickel

#### CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



#### PRODUCT SPECIFICATION

The show shall have air injected AeroJet+ technology. Product shall have 2.0 gpm (7.5 lpm) max. flow rate. Product shall have 12" diameter spray face. Product shall have rubber nozzels to prevent limescale build up. Product shall be **TOTO Model TS112BL12#\_\_\_.** 

# Please note the following components are sold separately:



TS110MV16 Shower Arm Wall Mount



TS110MC6 Shower Arm Ceiling Mount

## Classic Series Aero Rain Shower

#### **SPECIFICATIONS**

Warranty
Lifetime Limited Warranty


(Residential Use)

One Year (Commercial Use)

Material BrassShipping Weight 8.2 lbs.

• Shipping Dimensions 13-1/8" x 14-1/8" x 4-1/4"

Maximum Flow Rate 2.0 gpm (7.5 lpm)



### **INSTALLATION NOTES**

Required Components:

- TS110MV16 (Wall Mount Shower Arm)
- TS110MC6 (Ceiling Mount Shower Arm)

